



BURNDY Catalog Number
UPC Number
Description
Status

GC2929
 7818102317222
 2/0-250 CU-BAR (2)2PC GR
 Active

Web Use
 BURNDY Product Line

Width (in)
 Length (in)
 Height (in)
 Size (Hex) or Size (Bolt)
 Thickness
 Size (Hex) or Size (Bolt) - in
 Width (Fraction)

Dimensional
 2.04
 1.25
 2.32
 1/2
 0.25
 0.50
 2

Product Description

General

Mechanical Grounding Connector,
 2 Cables to 1/4" Thick Bar, 2/0
 AWG (Sol) -250 kcmil, 1/2"
 Stud, Torque:480 lb in

Bar Thickness (Range)
 Copper Solid Size (Range)
 Copper Stranded (Range)

Conductor(s)

1/4 in
 2/0 AWG-4/0 AWG
 2/0 AWG-250 kcmil

Installation Torque
 Type of Plating
 Plated (Yes or No)
 Product Material

Physical

480
 Unplated
 N
 Copper Alloy

Rated for Direct Burial
 UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS
 Industry Standards

Approvals / Certifications

Y
 Y
 Y
 Exempt
 N
 N
 UL467

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175